

ROTAX® ENGINE	600R E-TEC	900 ACE
Engine details	Liquid-cooled, 3-D R.A.V.E.™	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	2	3
Displacement	599.4 cc	899.0 cc
Bore	72,3 mm	74 mm
Stroke	73 mm	69.7 mm
Maximum engine speed	8100 RPM	7250 RPM
Carburation	Electronic Direct Injection	EFI
Recommended fuel type	Unleaded	Unleaded
Minimum octane	95	95
Fuel tank	37 liters	37 liters
Oil tank capacity (2-stroke)	3.4 liters	

COLOUR	Black	
DIMENSIONS		
Vehicle overall length*	3530 mm	
Vehicle overall width	1120 mm (600R E-TEC) 1200 mm (900 ACE)	
Vehicle overall height	1490 mm	
Ski stance	921 mm (600R E-TEC) 996 mm (900 ACE)	
Track nominal width	406 mm	
Track nominal length	4141 mm	
Track profile height	59 mm Powder Max FlexEdge	

PRO 2021

Full Moon Silver/Orange/

## **POWERTRAIN**

Drive clutch type	pDrive with clickers (600R E-TEC) pDrive (900 ACE)	
Driven clutch type	QRS	
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder	

## **SUSPENSION**

Front suspension	LFS with bended lower A-Arms
Front shock	HPG 36
Rear suspension	EasyRide
Center shock	HPG 36
Rear shock	HPG 36

## **FEATURES**

Frame	Radien-X
Skis	Blade DS+
Seating	2-up light
Handlebar	U-type steel with hooks, low grab handle
Riser block height	140 mm
Starter	Electric (900 ACE) Electric and manual (600R E-TEC)
Reverse	RER (600R E-TEC) Mechanical (900 ACE)

Standard	
Standard	
7.2-in. wide digital display	
Extra high with side deflectors	
Standard	
Front	
Yes, in front compartment	



<sup>\*</sup> Vehicle overall length without snowflap.