

ROTAX® ENGINE	600R E-TEC
Engine details	Liquid-cooled, 3-D R.A.V.E.™
Cylinders	2
Displacement	599.4 cc
Bore	72,3 mm
Stroke	73 mm
Maximum engine speed	8100 RPM
Carburation	Electronic Direct Injection
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	37 liters
Oil tank capacity (2-stroke)	3.4 liters

COLOUR	Viper Red/Black/White
DIMENSIONS	
Vehicle overall length*	2940 mm
Vehicle overall width	1270 mm
Vehicle overall height	1230 mm
Ski stance	1080 mm
Track nominal width	381 mm
Track nominal length	3269 mm
Track profile height	41 mm Cobra

POWERTRAIN

Drive clutch type	pDrive with clickers
Driven clutch type	QRS
Brake system	RS brake with 4 piston caliber, plastic master cylinder

SUSPENSION

Front suspension	LFS
Front shock	KYB 40 HLCR Kashima
Rear suspension	PPS ² -3300
Center shock	KYB 46 HLCR Kashima
Rear shock	KYB 46 HLCR Kashima

FEATURES

,	
Frame	Radien
Skis	Blade XC
Seating	Sport, 1-up
Handlebar	U-type aluminium with hooks
Riser block height	90 mm
Starter	Manual
Reverse	RER
Heated throttle lever	Standard

Heated grips	Standard
Gauge	7.2-in. wide digital display
Mirrors	
Windshield	Extra low
Hitch	
Visor Plug front / rear	
12V power outlet	Yes, in front compartment



^{*} Vehicle overall length without snowflap.