

SHREDDER DS





ROTAX® ENGINE	850 E-TEC	850 E-TEC Turbo R	
Engine details	Liquid-cooled, two-stroke, 3-D R.A.V.E.™	Liquid-cooled, two-stroke, turbocharged, 3-D R.A.V.E.™	
Cylinders	2		
Displacement	849 cc		
Bore	82 mm		
Stroke	80.4 mm		
Maximum engine speed	7900 RPM		
Carburation	Electronic Direct Injection with additional booster injectors		
Recommended fuel type	Unleaded		
Minimum octane	91		
Fuel tank	36 liters		
Oil tank capacity (2-stroke)	3.4 liters		

DIMENSIONS	
Vehicle overall length*	3190 mm (3900) 3335 mm (4100)
Vehicle overall width	1055 mm
Vehicle overall height	1280 mm
Ski stance	863 mm
Track nominal width	381 mm / 15 in.
Track nominal length	3912 mm / 154 in. 4178 mm / 165 in.
Track profile height	76 mm / 3 in. PowderMax X-Light

PO	W	н	DT	D	٨	IN

Drive clutch type	pDrive with clickers
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, adjustable brake lever, aluminum master cylinder

3	U 3	PE	-17	3	U	N

Front suspension	LFS	
Front shock	KYB 36 Plus Kashima	
Rear suspension	PPS ² -DS+	
Center shock	KYB 36 Plus Kashima	
Rear shock	KYB 36 Plus Kashima	

DRY WEIGHT

Dry weight	3900: 204 kg	3900: 211 kg 4100: 216 kg
------------	--------------	------------------------------

FEATURES

Frame	Radien²
Skis	Blade DS+
Seating	Mountain Light, 1-up
Handlebar	U-type aluminum with hooks, low grab handle
Riser block height	120 mm
Starter	Manual with SHOT

Reverse	RER	
Heated throttle lever	Standard	
Heated grips	Standard	
Gauge	4.5" digital display / 10.25" Touchscreen Display	
USB power outlet	Yes, in front compartment	
LinQ attachment	2 pairs	



^{*}vehicle overall length without snowflap.